

IK10  
20J.

IP21

# Torino



## Wall or ceiling mounted fitting particularly suited for housing.

- Steel spinning and fixing plate finished in matt white polyester powder coat.
- Opal polycarbonate diffuser held against body by tamperproof screws.
- Electronic control gear on removable tray with fused plug & socket connector block.
- Provision for conduit entry in back.

MATT WHITE  
C46MATT SILVER  
C48



### LAMP OPTIONS

#### OPAL DIFFUSER

LED	Lamps	Temp	Load	Lum/lms	Efficacy	Weight
TOR2/1400NW/C46	LED Array	4000K	15W	1313lms	91lm/W	3.5KG
TOR2/1900NW/C46	LED Array	4000K	21W	1763lms	83lm/W	3.5KG

### FITTING OPTIONS\*Please note /CF10 will only work if combined with /MWSB or /MWSA, or an external presence detection sensor supplied by others

Matt silver finish	replace C46 with C48
Integral 3 hour duration emergency	add suffix /EM3
DALI dimming/monitoring	add suffix /DALI
Switch dimming	add suffix /DIM
Corridor function*	add suffix /CF10
Microwave sensor – Basic	add suffix /MWSB
IP44 upgrade	add suffix /IP44



### TORINO LED

