Arculus Recessed Tuneable White

IP65 | IK16 (150J) | Modular | Class I | Recessed | TM65/66

Secure Healthcare

Arculus Recessed Tuneable White is a ligature resistant luminaire for challenging environments including secure healthcare.

Standard Colours

Matt White | Matt Titanium

Product Information

Arculus Recessed Tuneable White can adjust colour temperatures to help influence our wellbeing and replicate our natural circadian rhythm. Cool colour temperatures can boost activity whilst warm colour temperatures can aid relaxation. The opal diffuser provides a soft lit appearance and the discreet side mounted fixing ensures a clean, unobtrusive aesthetic.

Arculus Recessed Tuneable White is designed to meet the requirements of "Design in Mental Health Network's (DiMHN) Testing Guidance for Products in Mental Health Facilities" rating LIG5-5, with a ligature resistant design to help prevent self-harming. It is designed to be disassembled and reinstated to ensure maintenance can be undertaken quickly and easily after anti-pick mastic application.

Applications include therapy rooms, communal areas, exercise areas and nurses stations.

This luminaire is designed for longevity and sustainability and adheres to our circular design principles. We conduct a circular economy assessment using TM66 and measure embodied carbon (kgCO $_2$e) in accordance with TM65.2.

Impact Resistance Rating: IK16 (150J). What is IK Rating?
Ingress Protection Rating: IP65 (from below only). What is IP Rating?
Housing: Mild steel body, zinc coated steel frame.
Paint: Polyester powder coat. All Colour Options Available Here.
Diffuser: Flush opal polycarbonate diffuser in frame with side mounted tamperproof fixings.
Driver: Electronic control gear on a removable tray for ease of repair/upgrade with fused plug & socket connector block. DALI (Device type 8) driver as standard. Controlled by DALI control system (additional control devices required).
Mounting: Ceiling, recessed.
Cable Entry: Supplied with 1m flying lead in the back.
Design Life: 30+ years. What is Design Life?

Technical Information

ArculusRecessedTuneableWhite	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
Opal				
ARC-4300T-MW-R-DA	4395 @4000K	40.4	109	2700-6500
	Weight (kg)	**CRI**	**High Temp (°C)**	**LED Lifetime**
	14.4	CRI>90	-	$L_{80}B_{10}$>72,000h
	Driver lifetime (up to hours)	**LED Energy Rating**	**Emergency Output (Lum/lm)**	**Nightlight Output (Lum/lm)**
	100,000	D	-	-
	Dimensions			
	628mm x 628mm x 161mm			

Fitting Options

Matt White	-MW
Matt Titanium	-MT
Casambi Wireless Node	-DW
DALI-2 Dimming / Monitoring	-DA

- For paint colour options, please replace -MW with required paint code.
- For Casambi Node version, please replace -DA with DW.
- For Casambi User interface (White), order code CAUI-W.
- For Casambi User interface (Black), order code CAUI-B.



Arculus Recessed Tuneable White Drawing



Arculus Recessed Tuneable White Polar Curve



Arculus Recessed Tuneable White Minimum Ceiling Void and Ceiling Cut-out

Casambi User Interface (White). For Casambi User Interface (White), order code CAUI-W. For Casambi User Interface (Black), order code CAUI-B.

designplan LIGHTING

Tel: 020 8254 2000 | Email: sales@designplan.co.uk | Web: designplan.co.uk
Designplan Lighting Ltd. 16 Kimpton Park Way, Sutton, Surrey, United Kingdom, SM3 9QS | Registered in England No. 784246