



Tuscan Class II



Transport

Tuscan Class II is a vandal resistant luminaire specifically designed for transport applications.

Standard Colours



Product Information

Tuscan Class II's opal diffuser provides a soft lit appearance, while providing uniform illumination, ensuring a consistent light distribution. Incorporating a removable gear tray ensures Tuscan Class II is quick and easy to maintain, whilst enabling sustainable technology upgrades.

Applications include station forecourts, covered platforms, stairs and footbridges.

Impact Resistance Rating: IK16 (150J). More information, [CLICK HERE](#).

Ingress Protection Rating: IP65. More information, [CLICK HERE](#).

Housing: Zinc coated steel body.

Paint: Polyester powder coat. For all colours available, [CLICK HERE](#).

Diffuser: Opal polycarbonate diffuser in frame secured with tamperproof screws.

Driver: Electronic control gear on removable tray.

Mounting: Wall or ceiling.

Cable Entry: Provision for conduit entry in back and ends.

Technical Information

TuscanClassII	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L650mm				
D890-2-1500N-TB-CA	1419	15.5	92	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.8	CRI>80	45	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
	150mm x 80mm			

TuscanClassII	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L650mm				
D890-2-2200N-TB-CA	2059	22.5	92	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.8	CRI>80	45	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
	150mm x 80mm			
D890-2-1500W-TB-CA	1348	15.5	87	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.8	CRI>80	45	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	-	-
	Dimensions			
	150mm x 80mm			
D890-2-2200W-TB-CA	1956	22.5	87	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.8	CRI>80	45	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	-	-
	Dimensions			
	150mm x 80mm			
L1250mm				
D890-4-3200N-TB-CA	2990	33.7	89	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	8.7	CRI>80	45	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
	150mm x 80mm			
D890-4-4200N-TB-CA	3883	44.9	86	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	8.7	CRI>80	45	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
	150mm x 80mm			

TuscanClassII	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1250mm				
D890-4-3200W-TB-CA	2840	33.7	84	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	8.7	CRI>80	45	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	-	-
	Dimensions			
	150mm x 80mm			
D890-4-4200W-TB-CA	3689	44.9	82	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	8.7	CRI>80	45	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	-	-
	Dimensions			
	150mm x 80mm			
L1550mm				
D890-5-3700N-TB-CA	3420	37.3	92	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.2	CRI>80	45	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
	150mm x 80mm			
D890-5-5500N-TB-CA	4905	55.5	88	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.2	CRI>80	45	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
	150mm x 80mm			
D890-5-3700W-TB-CA	3249	37.3	87	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.2	CRI>80	45	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	-	-
	Dimensions			
	150mm x 80mm			

TuscanClassII	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1550mm				
D890-5-5500W-TB-CA	4660	55.5	84	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.2	CRI>80	45	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	-	-
	Dimensions			
	150mm x 80mm			

■ Fitting Options

Class II + Surge Protection + In-rush Limiter	-CB
Class II + Surge Protection	-CC
Anti-Graffiti Diffuser Coating	-AG
Coastal Paint Finish (Zone 2)	-Z2
Class II Only	-CA
Class II + In-rush Limiter	-CD
Fully Recessed	-R
DALI-2 Dimming / Monitoring	-DA
Emergency luminaire monitoring module (CEAG)	-EC
Textured White	-TW
Textured Black	-TB

- For paint colour options, please replace -TB with required paint code.
- HT Applies for standard version. For any options, please contact technical sales on +44 (0)20 8254 2022 or email technical@designplan.co.uk.
- -EC not available on 650mm versions, 1550mm 5500lm version, or recessed versions.
- For Class II product with Surge Protection and In-rush Limiter, please replace -CA with -CB.
- For Class II product with Surge Protection, please replace -CA with -CC.
- For Class II product with In-rush Limiter, please replace -CA with -CD.

