



## Terminus Wall

IP65

IK11 (50J)

Downlights

Class I

Surface

HT40°C

Community and Public

Transport

Terminus Wall is a vandal resistant luminaire specifically designed for transport applications and community and public installations.

Standard Colours

Matt White

Matt Silver

Matt Titanium

### Product Information

Terminus Wall's uniform illumination ensures a consistent light distribution, enhancing visibility and reducing glare. Incorporating a removable gear tray ensures Terminus Wall is quick and easy to maintain, whilst enabling sustainable technology upgrades.

Community and Public applications include the exterior and perimeter of buildings. Transport applications include station forecourts.

This luminaire is designed for longevity and sustainability and adheres to our circular design principles. We conduct a circular economy assessment using [TM66](#) and measure embodied carbon (kgCO<sub>2</sub>e) in accordance with [TM65.2](#).

**Impact Resistance Rating:** IK11 (50J). [What is IK Rating?](#)

**Ingress Protection Rating:** IP65. [What is IP Rating?](#)

**Housing:** Extruded and die cast aluminium body.

**Paint:** Polyester power coat. [All Colour Options Available Here.](#)

**Diffuser:** Clear polycarbonate diffuser.

**Driver:** Integral electronic control gear with terminal box.

**Mounting:** Wall.

**Cable Entry:** Provision for cable entry into terminal box.

**Design Life:** 30+ years. [What is Design Life?](#)

## ■ Technical Information

TerminusWall	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
<b>Wide Beam</b>				
TMW-1100NW-C-MT	966	8.3	117	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L <sub>80B10</sub> >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	544	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMW-2000NW-C-MT	1674	14.2	118	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L <sub>80B10</sub> >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	544	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMW-3000NW-C-MT	2367	19.8	119	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L <sub>80B10</sub> >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	544	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMW-4500NW-C-MT	3635	31.2	116	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L <sub>80B10</sub> >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	544	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMW-1100WW-C-MT	918	8.3	111	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L <sub>80B10</sub> >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	516	-
	Dimensions			
	Ø184mm, 290mm, 275mm			

TerminusWall	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
<b>Wide Beam</b>				
TMW-2000WW-C-MT	1590	14.2	112	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L <sub>80</sub> B <sub>10</sub> >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	516	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMW-3000WW-C-MT	2249	19.8	114	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L <sub>80</sub> B <sub>10</sub> >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	516	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMW-4500WW-C-MT	3453	31.2	111	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L <sub>80</sub> B <sub>10</sub> >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	516	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
<b>Medium Beam</b>				
TMW-1100NM-C-MT	943	8.2	115	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L <sub>80</sub> B <sub>10</sub> >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	527	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMW-2000NM-C-MT	1664	14.2	117	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L <sub>80</sub> B <sub>10</sub> >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	527	-
	Dimensions			
	Ø184mm, 290mm, 275mm			

TerminusWall	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
<b>Medium Beam</b>				
TMW-3000NM-C-MT	2332	20.1	116	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L <sub>80</sub> B <sub>10</sub> >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	527	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMW-4500NM-C-MT	3511	31.2	113	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L <sub>80</sub> B <sub>10</sub> >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	527	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMW-1100WM-C-MT	896	8.2	109	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L <sub>80</sub> B <sub>10</sub> >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	500	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMW-2000WM-C-MT	1581	14.2	111	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L <sub>80</sub> B <sub>10</sub> >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	500	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMW-3000WM-C-MT	2215	20.1	110	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L <sub>80</sub> B <sub>10</sub> >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	500	-
	Dimensions			
	Ø184mm, 290mm, 275mm			

TerminusWall	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
<b>Medium Beam</b>				
TMW-4500WM-C-MT	3335	31.2	107	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L <sub>80</sub> B <sub>10</sub> >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	500	-
	<b>Dimensions</b>			
	Ø184mm, 290mm, 275mm			
<b>Wide Up/Down</b>				
TMWD-1100NW-C-MT	966/966 (Down/Up)	15.2	127	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	-	L <sub>80</sub> B <sub>10</sub> >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	544	-
	<b>Dimensions</b>			
	Ø184mm, 290mm, 275mm			
TMWD-2000NW-C-MT	1674/1674 (Down/Up)	25.2	133	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	-	L <sub>80</sub> B <sub>10</sub> >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	544	-
	<b>Dimensions</b>			
	Ø184mm, 290mm, 275mm			
TMWD-1100WW-C-MT	918/918 (Down/Up)	15.2	121	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	-	L <sub>80</sub> B <sub>10</sub> >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	516	-
	<b>Dimensions</b>			
	Ø184mm, 290mm, 275mm			
TMWD-2000WW-C-MT	1590/1590 (Down/Up)	25.2	126	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	-	L <sub>80</sub> B <sub>10</sub> >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	516	-
	<b>Dimensions</b>			
	Ø184mm, 290mm, 275mm			

TerminusWall	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
<b>Medium Up/Down</b>				
TMWD-1100NM-C-MT	943/943 (Down/Up)	15.2	124	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	4.5	CRI>80	-	L <sub>80</sub> B <sub>10</sub> >60,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	527	-
	<b>Dimensions</b>			
	Ø184mm, 290mm, 275mm			
TMWD-2000NM-C-MT	1664/1664 (Down/Up)	25.2	132	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	4.5	CRI>80	-	L <sub>80</sub> B <sub>10</sub> >60,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	527	-
	<b>Dimensions</b>			
	Ø184mm, 290mm, 275mm			
TMWD-1100WM-C-MT	896/896 (Down/Up)	15.2	118	3000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	4.5	CRI>80	-	L <sub>80</sub> B <sub>10</sub> >60,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	500	-
	<b>Dimensions</b>			
	Ø184mm, 290mm, 275mm			
TMWD-2000WM-C-MT	1581/1581 (Down/Up)	25.2	125	3000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	4.5	CRI>80	-	L <sub>80</sub> B <sub>10</sub> >60,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	500	-
	<b>Dimensions</b>			
	Ø184mm, 290mm, 275mm			

## ■ Fitting Options

Maintained Emergency 3 Hour in Remote Box	-EB
Change Over Relay, 240V Relay Supplied	-ER
Central Battery Maintained 110V	-EV
Matt White	-MW
Matt Silver	-MS
Matt Titanium	-MT
DALI-2 Dimming / Monitoring	-DA

- For paint colour options, please replace -MT with required paint code.
- HT Applies to standard version. For any options (e.g. -E3), please check with technical sales.
- For Post Top version, please contact technical sales on +44 (0)20 8254 2022 or email [technical@designplan.co.uk](mailto:technical@designplan.co.uk).
- Upward light only available on 1100lm and 2000lm versions.
- For -EB option, please note that remote box is IP65 rated.

