



Tuscan 88 Angled S12

IP65

IK08 (5J)

Linear

Class I

Surface

TM65/66

Tuscan 88 Angled S12 is a vandal resistant luminaire specifically designed in accordance with fire precautions for subsurface rail stations (Section 12).

Standard Colours

Textured Black

Pure White

Textured White

Smooth White

- Product Information

Tuscan 88 Angled S12 directs light precisely where it's needed, reducing wasted illumination and minimising glare. Incorporating a removable gear tray ensures Tuscan 88 Angled S12 is quick and easy to maintain, whilst enabling sustainable technology upgrades.

Tuscan 88 Angled S12 complies with London Underground subsurface standard S1085 utilising low smoke, zero halogen cables and control gear.

This luminaire is designed for longevity and sustainability and adheres to our circular design principles. We conduct a circular economy assessment using [TM66](#) and measure embodied carbon (kgCO₂e) in accordance with [TM65.2](#).

Impact Resistance Rating: IK08 (5J). [What is IK Rating?](#)

Ingress Protection Rating: IP65. [What is IP Rating?](#)

Housing: Zinc coated steel body.

Paint: Polyester powder coat. [All Colour Options Available Here.](#)

Diffuser: Frosted toughened glass diffuser in frame secured with tamperproof screws.

Driver: Electronic control gear on removable tray for ease of repair/upgrade with fused plug & socket connector block.

Mounting: Cornice mounting at either 45° or 30°/60°.

Cable Entry: N/A (Blank body).

Design Life: 30+ years. [What is Design Life?](#)

■ **Technical Information**

Tuscan88Angled512	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L700mm x H188mm x W139mm - 30/60 Degree angle				
D882-2-1500N-F-TB-ST	1357	12.9	105	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	6.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	495	-
	Dimensions			
D882-2-2000N-F-TB-ST	1625	15.4	106	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	6.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	495	-
	Dimensions			
D882-2-2500N-F-TB-ST	1867	17.5	107	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	6.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	495	-
	Dimensions			
D882-2-3000N-F-TB-ST	2171	20.1	108	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	6.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	495	-
	Dimensions			
D882-2-1500W-F-TB-ST	1289	12.9	100	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	6.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	470	-
	Dimensions			

Tuscan88AngledS12	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L700mm x H188mm x W139mm - 30/60 Degree angle				
D882-2-2000W-F-TB-ST	1544	15.4	100	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	6.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	470	-
	Dimensions			
D882-2-2500W-F-TB-ST				
D882-2-2500W-F-TB-ST	1774	17.5	101	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	6.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	470	-
	Dimensions			
D882-2-3000W-F-TB-ST				
D882-2-3000W-F-TB-ST	2062	20.1	103	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	6.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	470	-
	Dimensions			
L1300mm x H188mm x W139mm - 30/60 Degree angle				
D882-4-2000N-F-TB-ST				
D882-4-2000N-F-TB-ST	1939	17.8	109	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	9.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	610	-
	Dimensions			
D882-4-3000N-F-TB-ST				
D882-4-3000N-F-TB-ST	2530	22.9	111	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	9.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	610	-
	Dimensions			

Tuscan88Angled512	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1300mm x H188mm x W139mm - 30/60Degree angle				
D882-4-4000N-F-TB-ST	3028	27.3	111	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	9.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	610	-
	Dimensions			
D882-4-5000N-F-TB-ST	3881	34.9	111	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	9.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	610	-
	Dimensions			
D882-4-6000N-F-TB-ST	4142	37.8	110	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	9.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	610	-
	Dimensions			
D882-4-2000W-F-TB-ST	1842	17.8	103	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	9.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	579	-
	Dimensions			
D882-4-3000W-F-TB-ST	2404	22.9	105	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	9.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	579	-
	Dimensions			

Tuscan88Angled512	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1300mm x H188mm x W139mm - 30/60 Degree angle				
D882-4-4000W-F-TB-ST	2877	27.3	105	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	9.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	579	-
	Dimensions			
L1300mm x H188mm x W139mm - 30/60 Degree angle				
D882-4-5000W-F-TB-ST	3687	34.9	106	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	9.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	579	-
	Dimensions			
L1300mm x H188mm x W139mm - 30/60 Degree angle				
D882-4-6000W-F-TB-ST	3935	37.8	104	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	9.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	579	-
	Dimensions			
L1600mm x H188mm x W139mm - 30/60 Degree angle				
D882-5-2500N-F-TB-ST	2543	21.4	119	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	767	-
	Dimensions			
L1600mm x H188mm x W139mm - 30/60 Degree angle				
D882-5-3750N-F-TB-ST	3269	27.4	119	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	767	-
	Dimensions			

Tuscan88Angled512	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1600mm x H188mm x W139mm - 30/60Degree angle				
D882-5-5000N-F-TB-ST	3822	33.3	115	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	767	-
	Dimensions			
D882-5-6250N-F-TB-ST	4702	39.5	119	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	767	-
	Dimensions			
D882-5-7500N-F-TB-ST	5154	45.9	112	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	767	-
	Dimensions			
D882-5-2500W-F-TB-ST	2416	21.4	113	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	728	-
	Dimensions			
D882-5-3750W-F-TB-ST	3106	27.4	113	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	728	-
	Dimensions			

Tuscan88AngledS12	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1600mm x H188mm x W139mm - 30/60 Degree angle				
D882-5-5000W-F-TB-ST	3631	33.3	109	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	728	-
	Dimensions			
L700mm x H158mm x W158mm - 45 Degree angle				
D882-5-6250W-F-TB-ST	4467	39.5	113	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	728	-
	Dimensions			
D882-5-7500W-F-TB-ST	4896	45.9	107	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	728	-
	Dimensions			
L700mm x H158mm x W158mm - 45 Degree angle				
D883-2-1500N-F-TB-ST	1357	12.9	105	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.5	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	495	-
	Dimensions			
D883-2-2000N-F-TB-ST	1625	15.4	106	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.5	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	495	-
	Dimensions			

Tuscan88AngledS12	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L700mm x H158mm x W158mm - 45 Degree angle				
D883-2-2500N-F-TB-ST	1867	17.5	107	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.5	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	495	-
	Dimensions			
D883-2-3000N-F-TB-ST	2171	20.1	108	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.5	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	495	-
	Dimensions			
D883-2-1500W-F-TB-ST	1289	12.9	100	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.5	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	470	-
	Dimensions			
D883-2-2000W-F-TB-ST	1544	15.4	100	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.5	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	470	-
	Dimensions			
D883-2-2500W-F-TB-ST	1774	17.5	101	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.5	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	470	-
	Dimensions			

Tuscan88Angled512	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L700mm x H158mm x W158mm - 45 Degree angle				
D883-2-3000W-F-TB-ST	2062	20.1	103	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.5	CRI>80	-	L ₈₀ B ₁₀₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	470	-
	Dimensions			
L1300mm x H158mm x W158mm - 45 Degree angle				
D883-4-2000N-F-TB-ST	1939	17.8	109	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.1	CRI>80	-	L ₈₀ B ₁₀₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	610	-
	Dimensions			
D883-4-3000N-F-TB-ST	2530	22.9	111	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.1	CRI>80	-	L ₈₀ B ₁₀₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	610	-
	Dimensions			
D883-4-4000N-F-TB-ST	3028	27.3	111	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.1	CRI>80	-	L ₈₀ B ₁₀₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	610	-
	Dimensions			
D883-4-5000N-F-TB-ST	3881	34.9	111	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.1	CRI>80	-	L ₈₀ B ₁₀₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	610	-
	Dimensions			

Tuscan88Angled512	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1300mm x H158mm x W158mm - 45 Degree angle				
D883-4-6000N-F-TB-ST	4142	37.8	110	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	610	-
	Dimensions			
D883-4-2000W-F-TB-ST	1842	17.8	103	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	579	-
	Dimensions			
D883-4-3000W-F-TB-ST	2404	22.9	105	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	579	-
	Dimensions			
D883-4-4000W-F-TB-ST	2877	27.3	105	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	579	-
	Dimensions			
D883-4-5000W-F-TB-ST	3687	34.9	106	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.1	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	579	-
	Dimensions			

Tuscan88AngledS12	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1300mm x H158mm x W158mm - 45 Degree angle				
D883-4-6000W-F-TB-ST	3935	37.8	104	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.1	CRI>80	-	L ₈₀ B ₁₀₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	579	-
	Dimensions			
L1600mm x H158mm x W158mm - 45 Degree angle				
D883-5-2500N-F-TB-ST	2543	21.4	119	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12	CRI>80	-	L ₈₀ B ₁₀₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	767	-
	Dimensions			
D883-5-3750N-F-TB-ST	3269	27.4	119	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12	CRI>80	-	L ₈₀ B ₁₀₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	767	-
	Dimensions			
D883-5-5000N-F-TB-ST	3822	33.3	115	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12	CRI>80	-	L ₈₀ B ₁₀₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	767	-
	Dimensions			
D883-5-6250N-F-TB-ST	4702	39.5	119	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12	CRI>80	-	L ₈₀ B ₁₀₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	767	-
	Dimensions			

Tuscan88Angled512	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1600mm x H158mm x W158mm - 45 Degree angle				
D883-5-7500N-F-TB-ST	5154	45.9	112	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	767	-
	Dimensions			
D883-5-2500W-F-TB-ST	2416	21.4	113	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	728	-
	Dimensions			
D883-5-3750W-F-TB-ST	3106	27.4	113	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	728	-
	Dimensions			
D883-5-5000W-F-TB-ST	3631	33.3	109	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	728	-
	Dimensions			
D883-5-6250W-F-TB-ST	4467	39.5	113	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	728	-
	Dimensions			

Tuscan88Angled512	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1600mm x H158mm x W158mm - 45 Degree angle				
D883-5-7500W-F-TB-ST	4896	45.9	107	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12	CRI>80	-	Life>72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	728	-
	Dimensions			

Fitting Options

Coastal Paint Finish (Zone 2)	-Z2
Maintained Emergency 3 Hour, Self Test	-ES
Change Over Relay, 240V Relay Supplied	-ER
Central Battery Maintained 110V	-EV
Maintained Emergency 3 Hour, DALI	-ED
Maintained Emergency 3 Hour	-E3
Textured Black	-TB
Pure White	-PW
Textured White	-TW
Smooth White	-SW
Switch Dimming	-DI
DALI-2 Dimming / Monitoring	-DA

- For paint colour options, please replace -TB with required paint code.
- -ED option not available on all 700mm versions.

